

DRY-LAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

LPV1200 & LPV1600 DUO Systems



FUJIFILM

DRY-LAM takes lamination of On-Demand Digital Prints to a new level.

The **Drylam Duo System** takes care of all your wide format laminating needs. The system allows you to choose the best type of laminate for your application. Run cost effective thermal laminates on most paper stocks and porous materials. Pressure sensitive cold laminates are perfect for non porous synthetic stocks, or stocks that are heat sensitive, including applications such as floor graphics, decals, and signage.

www.drylam.com • P: 888-633-1973 • F: 866-473-0534
23220 W 84th Street • Shawnee, KS 66227

LPV1200/LPV1600 DUO System

DRYLAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

LPV1200 & LPV1600 DUO Systems

Safety Features:

- Emergency Shutoff buttons on top rear corners of the machine
- Nip area sensors stop roller advancement if tripped
- Nip area safety shield swings up for easy threading and cleaning



Key Features:

- Foot pedal web advance included
- Heavy duty roller stand included
- Mechanically actuated pressure gaps up to 1 inch
- Mandrels marked at 38" and 43" for easy film alignment
- Digital temperature readout for top and bottom nip rollers
- Runs thermal or PSA Films
- Includes cooling fans
- Includes release liner and output rewinders



| Model: | LPV1200 DUO System | LPV1600 DUO System |
|----------------------------------|----------------------------|----------------------------|
| Maximum Laminating Width: | 47 inches | 63 inches |
| Maximum Laminating Thickness: | 1 inch | 1 inch |
| Laminating Film Thickness: | 1.2 - 10 mil | 1.2 - 10 mil |
| Film Types: | PSA and Thermal | PSA and Thermal |
| Temperature Range: | Room Temperature to 270° F | Room Temperature to 270° F |
| Dual Temperature Control: | Upper and Lower | Upper and Lower |
| Heated Rollers Upper and Lower: | Room Temperature to 270° F | Room Temperature to 270° F |
| Speed: | 0 - 12 feet per minute | 0 - 12 feet per minute |
| Unwind Mandrels Upper and Lower: | 3" core | 3" core |
| PSA Liner take up Mandrel top: | 3" core | 3" core |
| Gross Weight Laminator: | 595 lbs | 704 lbs |
| Stand Included (weight): | 100 lbs | 130 lbs |
| Power Requirements: | 230VAC Single Phase | 230VAC Single Phase |
| Wattage: | 4000 | 5150 |
| Plug Type: | Nema N6-30P | Nema N6-30P |